



Optical Fiber Stripper

S218R-Plus



Exceptionally clean stripping

Compatible with 200 micron fibre

Easy Operation

Long Battery Capacity (10 Hours)



FURUKAWA FLECTRIC

Specification Applicable Fibers Optical fibers (glass) Cladding diameter 0.125mm Fiber count 1 to 12 Coating diameter (single fiber) 0.2 to 0.4mm Fiber ribbon size 0.25 to 0.4mm (thickness) 80 to 140°C (4 steps of temperature) Heating temperature Approx. 10 hours (Normal mode) Battery life Charging time Approx. 2.5 hours (with power off condition) DC: 11V - 14V Power supply AC: 100V - 240V: in use of S952 AC adapter Dimensions 125W x 48D x 41H mm Weight 260g (including battery) Temperature: 0 to 40°C Operating condition Humidity: Max. 95 %RH (no condensing)

Standard package

Part Name	Part Number	Q'ty
Main body	S218R-Plus-01	1
Battery	S944	1
AC adapter	S952	1
Bag for main body	S218X-04	1
Hexagon Wrench	S218X-07	1
Cleaning brush	VGC-01	1
Operation Manual	FTS-B553	1

Optional parts

Part Name	Part Number	Q'ty
Single fiber adapter	S218X-03	1
Spare Blade	S218X-88	1
Spacer *1	S218-22	1
Stand *2	S218X-23	1

^{*1} for adjustment of stripping length

Contact Us:

Furukawa electric co., Ltd.

Head Office:

Chiyoda-ku, Tokyo, 100-8322, Japan Tel: + 81 3 3286 3227 Fax: + 81 3 3286 3978 www.furukawa.co.jp

2-3, Marunouchi 2-chome,

 ${\tt fec.abr_opt_splicer@furukawaelectric.com} \quad {\tt splicers@furukawa.co.uk}$

Furukawa Electric Europe Ltd.

Furukawa House 77-85 Fulham Palace Road, London W6 8JD, U.K. Tel: + 44 (0) 20 7313 5300 Fax: + 44 (0) 20 7313 5310 www.furukawa.co.uk

North & South America: **OFS Fitel, LLC**

2000 Northeast Expressway Norcross, Georgia 30071, U.S.A Toll free: + 1 866 452 9516 Tel: + 1 678 783 1090 Fax: + 1 678 783 1093 www.ofsoptics.com splicers@ofsoptics.com

China: Furukawa Shanghai, Ltd. **Beijing Branch**

Room 314, Beijing Fortune Building, 60 Albert Street, #13-10 OG No.5, North Dongsanhuan Road, Beijing 100004 P.R. China Tel: + 86 10 8591 0608 Fax: + 86 10 8591 0609 www.furukawa-sh.cn

South East Asia: Furukawa Electric Singapore Pte. Ltd.

Albert Complex, Singapore 189969 Tel: + 65 6224 4686 Fax: + 65 6336 2635

comms@furukawa.com.sq

Export Control Regulations

The products and/or technical information presented in this publication may be subject to the application of the Foreign Exchange and Foreign Trade Act and other related laws and regulations in Japan. In addition, the Export Administration Regulations (EAR) of the United States may be applicable.

In cases where exporting or reexporting the products and/or technical information presented in this publication, customers are requested to follow the necessary procedures at their own responsibility and cost. Please contact the Ministry of Economy, Trade and Industry of Japan or the Department of Commerce of the United States for details about procedures.

^{*2} unit frame supporter

^{*} Please understand that contents of this catalog may change without notice.