

MDU/SFU

Splicing Box - J417, J418

The small splicing box for Single Family Unit (SFU).



J417

- Indoor
- Outdoor
- Demarcation point



J418

- Indoor
- Rosette

Features and Benefits

J417

- Outdoor application: IPX3 (IEC60529)
- Wall mount type
- Compact size: W115×H200×D30 mm
- Light weight by plastic body and cover
- SC connector termination is available (optional)
- Max. fusion splice: 4-fibers

J418

- Indoor application (Flame retardant material)
- Wall mount type
- Compact size: W120×H115×D16 mm
- Light weight by plastic body and cover
- Max. fusion splice: 4-fibers

Specification

Item		Specification	
Product name		J417	J418
Dimension (W×H×D mm)		115×200×30	120×115×16
Weight (kg)		0.2	0.1
Flame retardance		Cover: UL94, V-2 Main body: UL94, HB Cable clamp: UL94, V-0	Cover: UL94, HB Main body: UL94, HB Cable clamp: UL94, V-0
Mount condition		Indoor/outdoor wall mount type	Indoor wall mount type
Water proof		IPX3	—
Cable entry position		Bottom×2	Bottom×2, Top×1
Max. cable count/side	Drop cable (W2.0) or Indoor cable (W2.0)	4	
	Optical cord	2 (φ 2.0 mm) 4 (φ 1.5 mm)	
Max. single fiber fusion splice		4	
Max. SC connector joint		2	—

Wiring Diagram

